



Ultramastic ECO™

High-Performance Floor and Wall Tile Adhesive



DESCRIPTION

Ultramastic ECO is a premium, solvent-free adhesive with an excellent open time and terrific sag resistance.

FEATURES AND BENEFITS

- LEED-compatible
- Easy to trowel with excellent trowel-ridge hold for proper adhesive bonding

INDUSTRY STANDARDS AND APPROVALS

ANSI: Meets or exceeds A136.1, Type 1 standards

CGSB: Meets or exceeds 71-GP-22M, Type 1 standards

ISO 13007: Classification D1TE

<u>LEED Points Contribution</u>	<u>LEED Points</u>
MR Credit 5, Regional Materials*.....	Up to 2 points
IEQ Credit 4.1, Low-Emitting Materials – Adhesives & Sealants.....	1 point
IEQ Credit 4.3, Low-Emitting Materials – Flooring Systems	1 point

* Using this MAPEI product may help contribute to LEED certification of projects in the categories shown above. Points are awarded based on contributions of all project materials.

WHERE TO USE

- For installation of tiles up to 6" x 6" (15 x 15 cm) on floors, and up to 10" x 10" (25 x 25 cm) on walls
- For use with ceramic and porcelain tile, and ceramic and porcelain mosaics
- For tub and bath surrounds where service requirements do not exceed ANSI A136.1, Type 1, or CGSB 71-GP-22M (Canada), Type 1 standards
- For the installation of wall tile in intermittent wet conditions such as tub and shower surrounds with precast bases

LIMITATIONS

- Do not install over substrates containing asbestos.
- Do not use for exterior applications, steam rooms, shower floors or areas subject to water submersion.
- Do not apply over waterproofing membranes, particleboard, Masonite, chipboard, Luaun, gypsum floor-patching compounds, metal or similar dimensionally unstable substrates.
- Use only at temperatures between 50°F and 95°F (10°C and 35°C).
- Do not use for setting bathroom fixtures or grab bars.
- Do not use to set natural stone. For this installation, contact MAPEI's Technical Services for product recommendations.



SUITABLE SUBSTRATES

- Fully cured concrete
- Masonry block
- Cement mortars and leveling coats
- Cement backer units (CBUs) (see manufacturer's instructions for approval)
- Gypsum wallboard – interior dry walls only (to improve adhesion, prime with *Primer L™* or *Planicrete® AC*)
- APA or CANPLY Group 1 exterior-glue plywood for interior residential floors and countertops in dry areas (see TCA handbook for additional information)

Consult MAPEI's Technical Services Department for installation recommendations regarding substrates and conditions not listed.

SURFACE PREPARATION

- See MAPEI's Surface Preparation Requirements document for tile and stone installation systems at www.mapei.com.

MIXING

Note: Choose all appropriate safety equipment before use. Refer to Material Safety Data Sheet (MSDS) for more information.

- *Ultramastic ECO* is ready to use. No mixing is required.

PRODUCT APPLICATION

1. Read all installation instructions thoroughly before installation.
2. Use a typical notched trowel (see chart below) with sufficient depth to ensure proper transfer, covering at least 80% of the tile back.
3. Using the trowel's flat edge, spread the adhesive on the substrate. Apply additional material and comb the surface using the trowel's notched side to achieve an even-setting bed. Do not spread more adhesive than can be covered with tiles within 30 to 45 minutes. If skinning occurs, scrape off skin and replace with fresh adhesive.
4. Place the tiles firmly into the wet mortar. Push the tiles back and forth in a direction perpendicular to trowel lines, in order to collapse the mortar ridges and achieve maximum coverage. Ensure proper contact between mortar, tile and substrate by periodically lifting a few tiles to check for acceptable coverage.
5. Make all alignments and adjustments immediately (do not exceed 45 minutes).
6. Promptly use water to clean smudges from the face of the tiles while the adhesive is still fresh. Once adhesive has dried, clean with mineral spirits.
7. Provide for expansion and control joints as specified per TCA handbook, Detail EJ171, or TTMAC handbook 09.30.00, Detail 301MJ.

8. Wash hands and tools with water while the adhesive is still fresh.
9. Allow tiles to reach a firm set, and then grout with an appropriate MAPEI grout.

Note: Using mastics with porcelain tiles or in cool, moist conditions will extend the time required for firm set.

PROTECTION

- Protect containers from freezing in transit and storage. This product is freeze/thaw-stable at temperatures down to 0°F (-18°C). However, protect all water-based products from freezing. If this material is frozen, do not stir it until it has completely thawed.
- Provide for heated storage on site and deliver materials at least 24 hours before tilework begins.
- Protect from water until the adhesive has reached its final set.
- Floors: Keep free from traffic for at least 72 hours after installation. Plywood or stepping boards may be used after 24 hours when occasional stepping on the floor is unavoidable.
- Walls: Protect from impact, vibration and hammering on adjacent and opposite walls for at least 14 days after installation.

Product Performance Properties

ISO 13007 Classification

Classification Code	Classification Requirement	Test Results
D1 (normal mastic)	Shear adhesion strength; Shear adhesion strength after aging; Open time: tensile adhesion strength	Pass
T (vertical slip resistance)	Slip $\leq 0,5$ mm	Pass
E (extended open time)	$\geq 0,5$ N/mm ² after not less than 30 minutes	Pass

ANSI Specification

Test Method	ANSI Specification	Test Results
ANSI A136.1 – shear strength (7 days)	Dry ≥ 50 psi (0,34 MPa)	Pass
	Wet immersion ≥ 50 psi (0,34 MPa)	Pass
ANSI A136.1 – shear strength (28 days)	≥ 50 psi (0,34 MPa)	Pass




Shelf Life and Application Properties

Shelf life	2 years
------------	---------

Packaging

Product Code	Size
Canada 90791000	Pail: 1 U.S. qt. (946 mL)
Canada 90753000	Pail: 1 U.S. gal. (3,79 L)
U.S. 1040015; Canada 90763000	Pail: 3.5 U.S. gals. (13,2 L)

Approximate Product Coverages*

Typical Trowel	1 U.S. qt. (946 mL) Coverage	1 U.S. gal. (3,79 L) Coverage	3.5 U.S. gals. (13,2 L) Coverage
1/8" x 1/8" x 1/8" (3 x 3 x 3 mm) 	12.5 to 17.5 sq. ft. (1,16 to 1,63 m ²)	50 to 70 sq. ft. (4,65 to 6,50 m ²)	175 to 245 sq. ft. (16,3 to 22,8 m ²)
3/16" x 5/32" (4,5 x 4 mm) 	10 to 12.5 sq. ft. (0,93 to 1,16 m ²)	40 to 50 sq. ft. (3,72 to 4,65 m ²)	140 to 175 sq. ft. (13,0 to 16,3 m ²)
1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) 	6.3 to 8.8 sq. ft. (0,59 to 0,82 m ²)	25 to 35 sq. ft. (2,32 to 3,25 m ²)	87.5 to 123 sq. ft. (8,13 to 11,4 m ²)

* Trowel dimensions are width/depth/space. Actual coverages will vary according to substrate profile and tile type.

Ultramastic ECO™



RELATED DOCUMENTS

Reference Guide: Surface Preparation Requirements for tile and stone installation systems	RGTO309*
---	----------

* At www.mapei.com.

Refer to MAPEI's Material Safety Data Sheet (MSDS) for specific data related to VOCs, health and safety, and handling of product.

STATEMENT OF RESPONSIBILITY

Before using, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

We proudly support the following industry organizations:



MAPEI Headquarters of the Americas
 1144 East Newport Center Drive
 Deerfield Beach, Florida 33442
 Phone: 1-888-US-MAPEI
 (1-888-876-2734)

Technical Services
 1-800-992-6273 (U.S. and Puerto Rico)
 1-800-361-9309 (Canada)

Customer Service
 1-800-42-MAPEI (1-800-426-2734)

For the most current BEST-BACKED™ product data and warranty information, visit www.mapei.com.

Edition Date: June 9, 2010
 PR110 UMED_F10Ev © 2010 MAPEI Corporation.
 All Rights Reserved. Printed in the USA.